

# CMS-200

## Control room management suite



Barco's CMS-200 software is an advanced control room management suite which allows for easy display wall management, efficient collaboration and fast decision-making in any control room. Barco's control room management suite provides operators and decision-makers with easy access to information and allows them to connect to information, to configure how it is displayed, and to collaborate in the most efficient way.

### **Connect**

Thanks to its networked concept, Barco's CMS-200 software enables users to easily connect to a multitude of sources, regardless of where the information has to be presented - on small LCD displays, video walls or operator workstations. Since all sources are available over the network, no dedicated hardware is necessary to visualize the information.

### **Control**

Barco's CMS-200 software offers nearly unlimited possibilities to control and manage displays and sources. Thanks to the usability-engineered CMS environment, managing information is done intuitively.

### **Collaborate**

With CMS-200, Barco has redefined control room collaboration. Through the unique concept of Perspectives, CMS allows to make more efficient use of the control room display estate, and to share user-defined information views with colleagues more efficiently.

**BARCO**

Visibly yours

# Features and compatibility requirements

## Features

### Central Server

- Central setup & connection management
- Central configuration database
- Fully distributed & modular component technology
- Fast set-up
- Browser based user interface
- Auto-detection of network sources
- **Control Panel**
  - Online configuration of sources, displays & system variables
  - Backup & restore capabilities
  - Advanced remote logging
- **Integration**
  - Fully featured Web services based API covering all functions
  - Legacy RS-232 and TCP/IP API support
- Apollo compatible API
- Audit trail support (NERC, CIP-7)
- **Authorization & security:**
  - User management
  - Active directory & LDAP support
  - Roles & permissions

### Client Software

- Zero maintenance
- Automatically saves the user's work
- **Sidebar**
  - Minimal use of screen estate
  - Live search for fast browsing
  - Source browser to open any source quickly
  - Fully drag and drop enabled
  - Minimal learning curve
  - Audio decoding of video streams
  - Full resolution and frame rate preview of all supported sources
- **Mini Display**
  - Remotely monitor displays over the network with the actual preview of all sources shown
  - Drag and drop from sidebar to mini display for quick perspective changes
  - Integrated soft KVM for remote control of displays
- **Perspectives**
  - One window with multiple sources
  - Perspectives can be opened and shown on both workstations and displays alike
  - Standard and custom tiling configuration
  - Share perspectives with other workstations or displays
  - Integrated soft KVM for remote control of sources
  - Decorators including: UMD, IDC, Source Name, Time (time zone aware), Date, Text, Logo, Message Ticker, Source status

### Display Agent

- Save and load layouts (complete display presets including perspectives and applications)
- **Desktop Manager**
  - Start, stop and position applications & sources freely over the complete desktop
- **Remote Pointer**
  - Remote keyboard and mouse control from and towards other networked desktops (bi-directional)

### Supported sources

- Analog & Streaming Video (compatibility list on request)
- Analog (RGB) and Digital (DVI-I)
- Networked desktops (VNC)
- Networked multi-channel workstations and Applications (Pro Sources)
- Intranet & Internet
- Barco JPEG 2000 streams
- Embedded & external audio formats

## Compatibility requirements

### Central Server

- Any Windows 7 Ultimate 64 bit, Windows Server 2008 R2 64bit, Windows Server 2012 64bit Server (Note: Microsoft Windows XP SP3 support was discontinued with CMS version 2.5)
- Barco provided IBM/Dell dual Xeon server
- Minimum 150 GB free hard disk space
- Minimum 4 GB memory
- At least 3.0 GHz quad core CPU or equivalent

### Display controllers

- Any Microsoft Windows XP SP3 32bit, Windows 7 Ultimate 32 bit, Windows 7 Ultimate 64 bit PC
- Nvidia Quadro 2000D preferred for full feature support
- Frame Grabber support (in Barco controllers)
- Minimum 10 GB free hard disk space
- Minimum 4 GB memory
- At least 2.16 GHz quad core CPU or equivalent

### Sidebar

- Any Microsoft Windows XP SP3 32bit, Windows 7 Ultimate 32 bit, Windows 7 Ultimate 64 bit PC
- Nvidia Quadro 2000D preferred for best feature support
- Frame Grabber support (in Barco controllers)
- Minimum 10 GB free hard disk space
- Minimum 2GB memory
- At least 2.16GHz dual core CPU or equivalent

M00320-R02-0214-DS February 2014

Barco is an ISO 9001 registered company.  
Technical specifications are subject to change without prior notice.  
The latest version of this product sheet can be found on [www.barco.com](http://www.barco.com)

Barco nv  
Pres. Kennedypark 35, B-8500 Kortrijk  
Europe, Middle-East, Africa: +32 56 26 20 09  
USA: +1 678 475 8000  
Latin America: +55 11 38421656  
Japan: +81 3 5762 8727  
China: +86 400 88 22726  
Or mail to [sales.security\\_and\\_monitoring@barco.com](mailto:sales.security_and_monitoring@barco.com)

**BARCO**

Visibly yours

[www.barco.com](http://www.barco.com)